

NEW VS PACKAGE AIR COOLED HIGH VACUUM BLOWERS

WITH PATENTED VENTURI
PRE-INJECTION SYSTEM ENGINEERING



MARKET LEADING THREE-LOBE POSITIVE DISPLACEMENT BLOWER TECHNOLOGY

VS packages air cooled, high-vacuum blowers offer a wide range of design features and incorporate energy efficiency improvements that comply with the strictest operational requirements of a wide range of applications.

This compact pressure and vacuum package is ideally suited for the rigorous demand of the vacuum truck market.



PACKAGE FEATURES

- SOUND REDUCTION
 UP TO 12 DBA
- COMPACT PLUG AND PLAY SYSTEM
- THREE-LOBE IMPELLER
 CONSTRUCTION WITH DUAL
 AIR INJECTION SYSTEM FOR
 A VACUUM UP TO 96%
- + CLEARANCES ADJUSTED AUTOMATICALLY DURING ASSEMBLY
- **LARGER** OIL CAPACITY
- + HIGH PERFORMANCE SEALING ARRANGEMENT USING 4 PISTON RINGS

PRODUCT BENEFITS

- **QUIETER** OPERATION
- **EASIER TO INSTALL** ON THE TRUCK FRAME
- NO OIL OR WATER COOLING SYSTEM (100% OIL FREE AIR)
- **EASIER MAINTENANCE**
- + RUNS COOLER
- **BETTER LUBRICATION**OF BEARINGS
- **LESS FREQUENT OIL CHANGES**



THE NEW VS SERIES PACKAGE WITH VENTURI PRE-INJECTION TECHNOLOGY


PROVIDING ADVANCED SOUND REDUCTION PERFORMANCE WITHOUT COMPROMISE


To gain a new level of efficiency, our renowned noise cancelling technology is engineered to keep the pulsation inside the blower for generating a sound wall.


This new dual air injection technology keeps the advantage of direct air injection and lowers the noise level.

VENTURI SYSTEM FLOW MECHANICS









◆ THE NEW VS PACKAGE

The direct injection of the VTB.XL Series is the most efficient solution to cool the blower and can work even with a closed valve at suction side (Inlet blanked off).





PRESSURE & VACUUM SOLUTIONS

SLIM PLUG & PLAY SOLUTION

EASY TO INSTALL & MAINTAIN



4-WAY VALVE (PNEUMATIC OR MANUAL)

OIL FILLING SYSTEM

SILENCER INLET/OUTLET (OPTIONAL)

BY PASS SYSTEM FOR FRESH AIR

VTB 820 VS

FILTER HOLDER INTEGRATED INTO THE PACKAGE

SILENCER COOL AIR INJECTION (OPTIONAL)





PRODUCT BENEFITS


| FEATURE | CUSTOMER VALUE |
|---|---|
| PLUG & PLAY | Simplifies assembly and reduces sourcing. Simply mount package to truck frame, plumb to tank or secondary shut-off / cyclone, and connect it to PTO or hydraulic motor. |
| • REDUCED SIZE | Compact design allows for a better fit either behind the cab or mounted on the frame. |
| EXTERNAL OIL FILLING SYSTEM | Easier for maintenance. |
| HIBON 4-WAY VALVE | With 50% less pressure drop than the competition, the result is a more efficient and cooler operation, providing improved pressure/vacuum performance and increased blower life through less restriction in air flow. |
| • WELDING FLANGE | Allows easy connection between truck tank and four-way valve. |
| FLANGE DN65 ON SILENCER TO COOL AIR INJECTION | Enables a 'tank breaker system' through the silencer for quieter operation. |
| ADDITIONAL STITCHING POINTS FOR SENSORS | Possibility to add two temperature sensors. |
| | |






TRUCK PACKAGE, **SCOPE & PERFORMANCE**

- **4-WAY VALVE**
- **VTB 820 VS**
- **OIL FILING SYSTEM**
- **FILTER**
- **SILENCER**
- SILENCER COOL AIR INJECTION
- **BY PASS SYSTEM FOR FRESH AIR**
- **CHECK VALVE**





PERFORMANCE

| VOLUME DISPLACEMENT (2822 m ³ /h)* | | | | | | | | | | | | | | |
|--|------------|----|------------|----|------------|----|------------|----|------------|----|------------|----|------------|----|
| SPEED (TR/MIN) | 30% VACUUM | | 40% VACUUM | | 50% VACUUM | | 60% VACUUM | | 70% VACUUM | | 80% VACUUM | | 90% VACUUM | |
| RPM | m³/h | kW |
| 2200 | 1333 | 17 | 1297 | 21 | 1237 | 26 | 1143 | 30 | 1032 | 34 | 858 | 36 | 258 | 40 |
| 2600 | 1611 | 20 | 1576 | 25 | 1520 | 31 | 1433 | 36 | 1322 | 40 | 1160 | 43 | 493 | 47 |
| 2800 | 1750 | 22 | 1715 | 27 | 1661 | 33 | 1577 | 39 | 1467 | 43 | 1311 | 47 | 611 | 51 |
| 3000 | 1888 | 23 | 1854 | 29 | 1802 | 36 | 1722 | 41 | 1613 | 46 | 1463 | 50 | 729 | 55 |
| 3200 | 2027 | 25 | 1993 | 31 | 1943 | 38 | 1867 | 44 | 1758 | 50 | 1614 | 54 | 846 | 59 |
| 3400 | 2166 | 27 | 2132 | 34 | 2085 | 41 | 2012 | 47 | 1903 | 53 | 1765 | 58 | 964 | 63 |
| 3600 | 2304 | 29 | 2272 | 36 | 2226 | 44 | 2156 | 50 | 2048 | 56 | 1916 | 62 | 1082 | 67 |
| 3800 | 2443 | 31 | 2411 | 39 | 2367 | 46 | 2301 | 52 | 2193 | 60 | 2067 | 65 | - | - |

^{*} Volume displacement at maximum speed.





TRUCK PACKAGE, **CONFIGURATION**



TRUCK PACKAGE VTB 820 BS CCW PB

VACUUM PUMP VTB 820 SHAFT CONFIGURATION **BOTTOM SHAFT** ROTATION CW CLOCKWISE CCW COUNTER CLOCKWISE 4-WAY VALVE OPTIONS **PNEUMATIC**

SILENCER OPTIONS

















DIMENSIONS (mm) TRUCK PACKAGE VTB 820 BS CW PB

















DIMENSIONS (mm) TRUCK PACKAGE VTB 820 BS CCW PB

















DIMENSIONS (mm) TRUCK PACKAGE VTB 820 TS CCW PN















DIMENSIONS (mm) TRUCK PACKAGE VTB 820 BS CW PN















www.hibon.com

INGERSOLL RAND AIR SOLUTIONS HIBON®

2 avenue Jean-Paul Sartre, 59290 Wasquehal France

T: +33 (0)3 20 45 39 39 **E:** hibon@irco.com

www.ingersollrand.com www.hibon.com

COMPRESSED AIR SYSTEMS AND SERVICES HIBON INC

100 Voyageur Pointe Claire Quebec, Canada H9R 6A8

T: +1 514 631-3501 **F:** +1 877 584 0307

www.hibon.com

Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.

